



◆ Application

- Measure the distance, automatic control , robot, X-Y labor ,printing, curtained door, shoe machine , textile machine and etc.

◆ Features

- Miniature size, easy assembling
- quadrature output channel (A&B) + index signal

◆ Ordering Information

ISC25	04	-	001E	-	360	BZ	1	-	5	L
ISC serial no. Φ25mm housing	Cable lead out : E= Cable lead out behind				Pulses P/R 100 200 250 360 400 500 ,1000,1024				Supply Voltage 5: 5V DC 5-30:5~30 VDC	Output Form E:Voltage L: Line Driver 26LS31/TTL K;Line driver 7272 F: Push-Pull C: Open Collector NPN CP: Open collector PNP
Shaft diameter 04=Φ4mm					Output signal A=A phase B=A,Bphase BZ=A,B Zphases		Width of Z signal Blank=no Z phase 1: TZ=1T 2: TZ=1/2T 3: TZ=1/4T			

◆ Note:

1.Please contact sales representative to confirm the correctness and availability of the part number

◆ Technical Specifications

Electrical Specification				
Output circuit	Open collector	Voltage output	Push pull output	Line driver output
Power Vcc	5~30	5~30	5±0.25 5~30	5±0.25 5~30
Current	≤80mA	≤80mA	≤80mA	≤150mA
Load current	40mA	40mA	40mA	60mA
High-level output	Min Vcc*70%	Min Vcc-2.5V	Min Vcc-1.5V	Min 3.4V
Low-level output	Max 0.4V	Max 0.4V	Max 0.8V	Max 0.4V
Rise Time Tr	Max 1us	Max 1us	Max 1us	Max 200ns
Fall Time Tr	Max 1us	Max 1us	Max 1us	Max 200ns
Max Responding Frequency	150kHz	150kHz	150kHz	150kHz
Mechanical Specification				
Max speed(r/min)	Starting Torque	Max. Shaft Loading	Shocking	Vibration
6000	<0.03Nm	Radial:15N, Axial:10N	50G/11ms	10G 10-2000Hz
Rotor Inertia	Working Temperature	Storage Temperature	Protection Grade	Weight
4*10 ⁻⁸ Kg·m ²	-25~80℃	-30~85℃	IP51	60g

◆ Connection Table

Signal	A	B	Z	Ā	Ē	Ž	Vcc	GND
Color	Green	White	Yellow	Brown	Grey	Orange	Red	Black

◆ Dimensions(mm)

